Shooting a sky diver falling at 120 mph, you've got enough on your mind.

So you choose Kodak film.



swinek

The New Swintek wireless microphone system incorporates state-of-the-art solid state circuitry. Tuning is automatically adjusted by a precision crystal element. Hi-Band operation, 150-220 MHZ, is virtually free of static, dead spots and interference common to Low-Band and current 88-108 MHZ systems. A signal to noise ratio in excess of 60 dB is typical for a distance of 100 feet.

Wireless Microphone System

MARK 111 VHF



TRANSMITTER FEATURES

- Powered by 9 V radio battery
- Accepts low impedence input and has internal level adjust
- Compressor/limiter to prevent acoustic overload
- Crystal controlled
- Dimensions 3.75" long 2.25" wide .85" thick

RECEIVER FEATURES

- Powered by 1.5 V Pencel AA battery or external 10-24 V supply
- LED Monitoring capability: audio, HF carrier level, battery
- Simultaneous audio outputs: balanced low level, unbalanced line.

MARKIVVHF

TRANSMITTER FEATURE

- High Input: Powers Sony ECM-50 microphone thru miniature phone plug with locking collar
- Low Input: Standard 50-250 Ohm low impedance mike input with miniature phone plug with locking collar
- Compressor Indicator LED: Allows the mike gain to be set at the transmitter
- Powered by 9VDC radio battery
- Internal Level adjust
- Compressor/limiter to prevent acoustic overload

RECEIVER FEATURES

- Crystal IF filter
- Operates on AC or DC
- Helical HF front end
- Monitoring capability: audio, HF carrier level,
- DC power pack
- Simultaneous audio outputs: balanced low level, unbalanced line
- Transmission indicator light
- Phone jack and volume control for headset monitoring



MARKVVHF



TRANSMITTER FEATURES

- Powered by 9V radio battery
- Completely self-contained hand-held radio microphone
- Durable, lightweight construction for lasting trouble free operation
- Wide dynamic range of audio circuitry eliminates excessive harmonic distortion
- Internal mike level adjust
- Crystal controlled

RECEIVER FEATURES

- Crystal IF filter
- Operates on AC or DC
- Helical HF front end
- Monitoring capability: audio, HF carrier level
- DC power pack
- Simultaneous audio outputs: balanced low level, unbalanced line
- Transmission indicator light
- Phone jack and volume control for headset monitoring



SALES & RENTALS

MOTION PICTURE STUDIO, CAMERA AND EQUIPMENT RENTALS

Phone or write — 41 Scollard St., Toronto M5R 1G1, 416-920-5424

Mailable seensing to waite of the Market of Steelisting to the Market of the Market of